

Han GND module, male




Image is for illustration purposes only. Please refer to product description.

Part number	09 14 001 3032
Specification	Han GND module, male
HARTING eCatalogue	https://b2b.harting.com/09140013032

Identification

Category	Inserts
Series	Han® GND

Version

Termination method	Crimp termination Axial screw termination
Gender	Male
Number of contacts	1
Details	Please order contacts separately.

Technical characteristics

Conductor cross-section	10 ... 35 mm²
Insulation resistance	>10 ¹⁰ Ω
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500

Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	Yellow
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e



Pushing Performance
Since 1945

Material properties

REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Requirement set with Hazard Levels	R26

Specifications and approvals

Specifications	IEC 60664-1
	IEC 61984
UL / CSA	UL 1977 ECBT2.E235076

Commercial data

Packaging size	2
Net weight	9.04 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140019331
ETIM	EC000438
eCl@ss	27440205 Contact insert for industrial connectors