



Pushing Performance  
Since 1945

# Han C axial module, male 2,5-8mm<sup>2</sup>



Image is for illustration purposes only. Please refer to product description.

Part number	09 14 003 2601
Specification	Han C axial module, male 2,5-8mm <sup>2</sup>
HARTING eCatalogue	<a href="https://b2b.harting.com/09140032601">https://b2b.harting.com/09140032601</a>

## Identification

Category	Modules
Series	Han-Modular <sup>®</sup>
Type of module	Han <sup>®</sup> C module
Size of the module	Single module

## Version

Termination method	Axial screw termination
Gender	Male
Number of contacts	3

## Technical characteristics

Conductor cross-section	2.5 ... 8 mm <sup>2</sup>
Rated current	40 A
Rated voltage	690 V
Rated impulse voltage	8 kV
Pollution degree	3
Rated current acc. to UL	40 A
Rated voltage acc. to UL	600 V
Insulation resistance	>10 <sup>10</sup> Ω
Contact resistance	≤0.3 mΩ
Stripping length	5 mm @ 2.5 mm <sup>2</sup>
	5 mm @ 4 mm <sup>2</sup>
	8 mm @ 6 mm <sup>2</sup>



Pushing Performance  
Since 1945

## Technical characteristics

Tightening torque	1.5 Nm @ 2.5 mm <sup>2</sup>
	1.5 Nm @ 4 mm <sup>2</sup>
	2 Nm @ 6 mm <sup>2</sup>
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	5dbb3851-b94e-4e88-97a1-571845975242
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Specifications	IEC 60664-1
	IEC 61984
UL / CSA	UL 1977 ECBT2.E235076
	UL 2237 PVVA2.E318390
	CSA-C22.2 No. 182.3 PVVA8.E318390
Approvals	DNV GL



**Pushing Performance**  
Since 1945

## Commercial data

Packaging size	2
Net weight	32 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140019997
ETIM	EC000438
eCl@ss	27440217 Module for industrial connectors (power/signals)