

Han 10A-Cover-Plastic 2 Pins, f. BP



Part number	09 20 010 5410
Specification	Han 10A-Cover-Plastic 2 Pins, f. BP
HARTING eCatalogue	https://b2b.harting.com/09200105410

Image is for illustration purposes only. Please refer to product description.

Identification

Series of hoods/housings Han A® Type of accessory Protection cover Description of the accessory for bearing pedestal Version Version Size 10 A Locking type Single locking lever Technical characteristics Initing temperature Limiting temperature -40 +125 °C Degree of protection acc. to IEC 60529 IP65		
Type of accessoryProtection coverDescription of the accessoryfor bearing pedestalVersionSize10 ALocking typeSingle locking leverTechnical characteristicsLimiting temperature-40 +125 °CDegree of protection acc. to IEC 60529IP65Material properties	Category	Accessories
Description of the accessory for bearing pedestal Version Image: Size image: Si	Series of hoods/housings	Han A [®]
Version Size 10 A Locking type Single locking lever Technical characteristics Limiting temperature -40 +125 °C Degree of protection acc. to IEC 60529 IP65 Material properties	Type of accessory	Protection cover
Size10 ALocking typeSingle locking leverTechnical characteristics-40 +125 °CLimiting temperature-40 +125 °CDegree of protection acc. to IEC 60529IP65Material properties-40 +125 °C	Description of the accessory	for bearing pedestal
Size10 ALocking typeSingle locking leverTechnical characteristicsLimiting temperature-40 +125 °CDegree of protection acc. to IEC 60529IP65Material properties		
Locking type Single locking lever Technical characteristics Imiting temperature Limiting temperature -40 +125 °C Degree of protection acc. to IEC 60529 IP65 Material properties IP65	Version	
Technical characteristics Limiting temperature -40 +125 °C Degree of protection acc. to IEC 60529 IP65 Material properties	Size	10 A
Limiting temperature -40 +125 °C Degree of protection acc. to IEC 60529 IP65 Material properties IP65	Locking type	Single locking lever
Limiting temperature -40 +125 °C Degree of protection acc. to IEC 60529 IP65 Material properties IP65		
Degree of protection acc. to IEC 60529 IP65 Material properties	Technical characteristics	
Material properties	Limiting temperature	-40 +125 °C
	Degree of protection acc. to IEC 60529	IP65
Material (accessories) Thermoplastic	Material properties	
······	Material (accessories)	Thermoplastic
RoHS compliant	RoHS	compliant
ELV status compliant	ELV status	compliant
China RoHS e	China RoHS	e
	REACH Annex XVII substances	Not contained
	REACH ANNEX XIV substances	Not contained

Material (accessories)	Thermoplastic
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes



Material properties

California Proposition 65 substances	Nickel Naphthalene
Commercial data	
Packaging size	1
Net weight	18.3 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140039537
ETIM	EC002314
eCl@ss	27440208 Cap for industrial connectors