

Han 3HvE-M-s



Part number	09 34 003 2601
Specification	Han 3HvE-M-s
HARTING eCatalogue	https://b2b.harting.com/09340032601

Image is for illustration purposes only. Please refer to product description.

Identification

Category	Inserts
Series	Han Hv E [®]

Version

Termination method	Screw termination
Gender	Male
Size	10 B
With wire protection	Yes
Number of contacts	5
Number of power contacts	3
Number of special contacts	2
Specification of special contacts	Relay contact
PE contact	Yes

Technical characteristics

Conductor cross-section	0.75 2.5 mm²
Conductor areas section	AWG 18 AWG 14
Conductor cross-section	AVVG 18 AVVG 14
Rated current	16 A
Rated voltage	830 V
Detect immules veltage	0.137
Rated impulse voltage	8 kV
Pollution degree	3
	•
Rated voltage acc. to UL	600 V
Rated voltage acc. to CSA	600 V
3	



Technical characteristics

Insulation resistance	>10 ¹⁰ Ω
Contact resistance	≤1 mΩ
Stripping length	7.5 mm
Tightening torque	0.5 Nm
Limiting temperature	-40 +125 °C
Mating cycles	≥500

Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate Lead
ECHA SCIP number	5dbb3851-b94e-4e88-97a1-571845975242
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
UL / CSA	UL 1977 ECBT2.E235076



Commercial data

Packaging size	1
Net weight	51.86 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140052963
ETIM	EC000438
eCl@ss	27440205 Contact insert for industrial connectors