

# Han M Hood Coupler 1 Lever PG 11



| Part number        | 09 37 003 1750                      |
|--------------------|-------------------------------------|
| Specification      | Han M Hood Coupler 1 Lever PG 11    |
| HARTING eCatalogue | https://b2b.harting.com/09370031750 |

Image is for illustration purposes only. Please refer to product description.

### Identification

| Category                 | Hoods/Housings         |
|--------------------------|------------------------|
| Series of hoods/housings | Han <sup>®</sup> M     |
| Type of hood/housing     | Cable to cable housing |

#### Version

| Size                 | 3 A                                   |
|----------------------|---------------------------------------|
| Version              | Top entry                             |
| Cable entry          | 1x Pg 11                              |
| Locking type         | Single locking lever                  |
| Field of application | Hoods/housings for rough environments |
| Pack contents        | With seal screw                       |

### Technical characteristics

| Limiting temperature                   | -40 +125 °C                                    |
|--|--|
| Note on the limiting temperature       | For use as a connector according to IEC 61984. |
| Degree of protection acc. to IEC 60529 | IP44 IP65 With seal screw IP67 With seal screw |

### Material properties

| Material (hood/housing) | Zinc die-cast        |
|-------------------------|----------------------|
| Surface (hood/housing)  | Powder-coated        |
| Colour (hood/housing)   | RAL 9005 (jet black) |
| Material (locking)      | Stainless steel      |

Page 1 / 2 | Creation date 2024-01-05 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application.

HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany

Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Material properties

| RoHS                                 | compliant                  |
|--------------------------------------|----------------------------|
| ELV status                           | compliant                  |
| China RoHS                           | e                          |
| REACH Annex XVII substances          | Not contained              |
| REACH ANNEX XIV substances           | Not contained              |
| REACH SVHC substances                | Not contained              |
| California Proposition 65 substances | Yes                        |
| California Proposition 65 substances | Lead<br>Nickel             |
| Fire protection on railway vehicles  | EN 45545-2 (2020-08)       |
| Requirement set with Hazard Levels   | R1 (HL 1-3)<br>R7 (HL 1-3) |

### Specifications and approvals

| CE        | Yes    |
|-----------|--------|
| Approvals | DNV GL |

### Commercial data

| Packaging size                 | 10                                       |
|--------------------------------|--|
| Net weight                     | 74 g                                     |
| Country of origin              | Romania                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140055254                            |
| ETIM                           | EC000437                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |