

## Han® S 200 FC CRT 25 mm² w. rubb. sleeve



Image is for illustration purposes only. Please refer to product description.

Part number	09 93 000 6262
Specification	Han® S 200 FC CRT 25 mm² w. rubb. sleeve
HARTING eCatalogue	<a href="https://b2b.harting.com/09930006262">https://b2b.harting.com/09930006262</a>

### Identification

Category	Contacts
Series	Han® S
Identification	Han® S 200
Type of contact	Crimp contact
Description of the contact	Female contact incl. rubber sleeve

### Version

Manufacturing process	Turned contacts
-----------------------	-----------------

### Technical characteristics

Conductor cross-section	25 mm²
Conductor cross-section	AWG 4
Rated current	≤200 A
Contact resistance	≤0.3 mΩ
Stripping length	22 mm

### Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (accessories)	Thermoplastic polyurethane (TPU)
RoHS	compliant
ELV status	compliant



Pushing Performance  
Since 1945

Material properties

China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained

Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
----------------	--------------------------

Commercial data

Packaging size	1
Net weight	44 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140188785
ETIM	EC000796
eCl@ss	27440204 Contact for industrial connectors