

## Han INOX 3A Bulkhead Mounted Housing



Image is for illustration purposes only. Please refer to product description.

|                    |                                                                                       |
|--------------------|---------------------------------------------------------------------------------------|
| Part number        | 19 44 003 0301                                                                        |
| Specification      | Han INOX 3A Bulkhead Mounted Housing                                                  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19440030301">https://b2b.harting.com/19440030301</a> |

### Identification

|                             |                             |
|-----------------------------|-----------------------------|
| Category                    | Hoods/Housings              |
| Series of hoods/housings    | Han-INOX®<br>Han® High Temp |
| Type of hood/housing        | Bulkhead mounted housing    |
| Description of hood/housing | Straight                    |

### Version

|                      |                                       |
|----------------------|---------------------------------------|
| Size                 | 3 A                                   |
| Locking type         | Single locking lever                  |
| Field of application | Hoods/housings for harsh environments |
| Pack contents        | With seal screw                       |

### Technical characteristics

|                                        |                                                                   |
|----------------------------------------|-------------------------------------------------------------------|
| Limiting temperature                   | -40 ... +125 °C<br>-40 ... +200 °C With Han® High Temp components |
| Note on the limiting temperature       | For use as a connector according to IEC 61984.                    |
| Degree of protection acc. to IEC 60529 | IP44<br>IP65 With seal screw<br>IP67 With seal screw              |
| Type rating acc. to UL 50 / UL 50E     | 4<br>4X<br>12                                                     |

### Material properties

|                         |                 |
|-------------------------|-----------------|
| Material (hood/housing) | Stainless steel |
|-------------------------|-----------------|



**Pushing Performance**  
Since 1945

## Material properties

|                                      |                       |
|--------------------------------------|-----------------------|
| Surface (hood/housing)               | Uncoated              |
| Colour (hood/housing)                | Unpainted             |
| Material (locking)                   | Stainless steel       |
| RoHS                                 | compliant             |
| ELV status                           | compliant             |
| China RoHS                           | e                     |
| REACH Annex XVII substances          | Not contained         |
| REACH ANNEX XIV substances           | Not contained         |
| REACH SVHC substances                | Not contained         |
| California Proposition 65 substances | Yes                   |
| California Proposition 65 substances | Nickel<br>Naphthalene |

## Specifications and approvals

|           |                                                            |
|-----------|------------------------------------------------------------|
| UL / CSA  | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| CE        | Yes                                                        |
| Approvals | DNV GL                                                     |

## Commercial data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Packaging size                 | 1                                        |
| Net weight                     | 44 g                                     |
| Country of origin              | Germany                                  |
| European customs tariff number | 85389099                                 |
| GTIN                           | 5713140131934                            |
| ETIM                           | EC000437                                 |
| eCl@ss                         | 27440202 Shell for industrial connectors |