

# Cicular Connector w. Harax 7/8" L5 M



| Part number        | 21 04 116 1505                       |
|--------------------|--------------------------------------|
| Specification      | Cicular Connector w. Harax 7/8" L5 M |
| HARTING eCatalogue | https://b2b.harting.com/21041161505  |

Image is for illustration purposes only. Please refer to product description.

## Identification

| Category      | Connectors               |
|---------------|--------------------------|
| Series        | Circular connectors 7/8" |
| Element       | Cable connector          |
| Specification | Straight                 |

#### Version

| Termination method | HARAX <sup>®</sup> connection technology |
|--------------------|--|
| Gender             | Male                                     |
| Shielding          | Unshielded                               |
| Number of contacts | 5  |
| Locking type       | Screw locking                            |

# Technical characteristics

| Conductor cross-section           | 0.75 1.5 mm²       |
|-----------------------------------|--------------------|
| Conductor cross-section           | AWG 18 AWG 16      |
| Wire outer diameter               | ≤2.8 mm            |
| Rated current                     | 10 A               |
| Rated voltage conductor-earth     | 230 V              |
| Rated voltage conductor-conductor | 400 V              |
| Rated impulse voltage             | 4.8 kV             |
| Pollution degree                  | 3                  |
| Overvoltage category              | III                |
| Insulation resistance             | >10 <sup>8</sup> Ω |



## Technical characteristics

| Contact resistance                        | ≤10 mΩ                      |
|---|-----------------------------|
| Tightening torque                         | 1.5 Nm                      |
| Wrench size (knurled screw / knurled nut) | 22                          |
| Limiting temperature                      | -40 +85 °C                  |
| Mating cycles                             | ≥100                        |
| Degree of protection acc. to IEC 60529    | IP65 / IP67 mated condition |
| Cable diameter                            | 6.8 12.5 mm                 |
| Isolation group                           | I (600 ≤ CTI)               |

# Material properties

| Material (insert)                    | Polyamide (PA) Thermoplastic polyurethane (TPU)               |
|--------------------------------------|---|
| Material (contacts)                  | Copper alloy  |
| Surface (contacts)                   | Au over Ni Mating side  |
| Material (hood/housing)              | Polyamide (PA) Zinc die-cast Thermoplastic polyurethane (TPU) |
| RoHS                                 | compliant with exemption                                      |
| RoHS exemptions                      | 6(c): Copper alloy containing up to 4 % lead by weight        |
| ELV status                           | compliant with exemption                                      |
| China RoHS                           | 50  |
| REACH Annex XVII substances          | Not contained   |
| REACH ANNEX XIV substances           | Not contained   |
| REACH SVHC substances                | Yes   |
| REACH SVHC substances                | Lead  |
| ECHA SCIP number                     | 0d7d3693-d625-47ab-934a-d241bf72c86e                          |
| California Proposition 65 substances | Yes   |
| California Proposition 65 substances | Lead<br>Nickel  |

#### Commercial data

| Packaging size                 | 1        |
|--------------------------------|----------|
| Net weight                     | 90 g     |
| Country of origin              | Romania  |
| European customs tariff number | 85366990 |

Product data sheet 21 04 116 1505 Cicular Connector w. Harax 7/8" L5 M



## Commercial data

| GTIN   | 5713140139831                                    |
|--------|--|
| ETIM   | EC002635   |
| eCl@ss | 27440116 Circular connector (for field assembly) |