


Product description	M8 Male cable connector - female angled connector M12x1, Contacts: 4, unshielded, moulded on the cable, IP67, UL, PUR, black, 4 x 0.34 mm ² , 1 m
Area	series 765
Part no.	77 3434 3405 50004-0100


Illustration



Scale drawing



Contact arrangement (Plug-in side)



Technical data

General features

Part no.

77 3434 3405 50004-0100

Alternative part no.: 79 5077 10 04

Please note that, due to the change from the old to the new order number, there may be deviations in the technical specifications. For questions about product details, please use the 'Contact Customer Service' form on the right.

Notice

Connector design

Male cable connector - female angled connector M12x1

Type standard

DIN EN 61076-2-104

DIN EN 61076-2-101

Cable length

1 m (Standard 1 m and 2 m. Other lengths are available on request.)

Version

Connecting cable

Connector locking system

screw

Termination

moulded on the cable

Degree of protection

IP67

Cross-sectional area

0.34 mm² / AWG 22

Temperature range from/to

-25 °C / 85 °C

Mechanical operation

> 100 Mating cycles

Weight (g)

29

Customs tariff number

85444290

Country of Origin

DE

Electrical parameters

Rated voltage	60 V
Rated impulse voltage	800 V
Rated current	4.0 A
Pollution degree	3
Overvoltage category	II
Insulating material group	II
EMC compliance	unshielded

Product description	M8 Male cable connector - female angled connector M12x1, Contacts: 4, unshielded, moulded on the cable, IP67, UL, PUR, black, 4 x 0.34 mm ² , 1 m
Area	series 765
Part no.	77 3434 3405 50004-0100

Material

Contact body material	PUR
Contact material	CuZn (brass)
Contact plating	Au (gold)
REACH SVHC	CAS 7439-92-1 (Lead)
SCIP number	f9312a52-6de7-4c3d-9d41-0e1409560172

Authorization/approvals

Approvals	UL
-----------	----

Classifications

ETIM 9.0	EC002638
----------	----------

Cable data - Structure of the cable

Cable diameter	4.7 mm
Cross section	4 x 0.34 mm ²
Sheath material	PUR
Single-lead insulation	PP9Y halogen-free
Single-lead structure	42 x 0.10 mm
Cable color	black

Cable data - Mechanical properties

Bending radius, fixed cable	≥ 5 x Ø
Bending radius, moving cable	≥ 10 x Ø
Bending cycles	> 5 million
Permitted acceleration	5 m/s ²
Travel speed	≤ 200 m/min (5 m horizontal distance)

Cable data - Thermal properties

Temperature range cable in move from/to	-25 °C / 90 °C
Temperature range cable fixed from/to	-50 °C / 90 °C